

- ✓ Powerful 1700 watt motor
- ✓ 20J impact energy for heavy demolition applications
- ✓ 50mm drilling capacity into concrete
- ✓ Variable speed electronics for control
- ✓ No load speed limitation
- ✓ AVS anti-vibration system significantly reduces vibration for user comfort and safety
- ✓ Safety clutch for user protection
- ✓ Soft start for precise start of drilling/chiselling
- ✓ Service light provides in-time notice in the case of worn out brushes



|  |               |
|--|---------------|
| Blow energy (EPTA)(J)  | 20            |
| EAN Code   | 4002395198931 |
| Full load hammer action (bpm)                                    | 975 - 1950    |
| Max. drilling concrete (mm)                                      | 50            |
| Max. drilling concrete/core bit/tunnel drill bit (mm)            | 50 / 150 / 80 |
| Max. drilling core bit (mm)                                      | 150           |
| Max. drilling tunnel bit (mm)                                    | 80            |
| No load speed (rpm)  | 125 - 250     |
| Power input (W)  | 1700          |
| Power output (W)   | 850           |
| Sound power level (Lwa)(dB(A))                                   | 111           |
| Sound power level uncertainty (dB(A))                            | 3             |
| Sound pressure level (Lpa)(dB(A))                                | 100           |
| Sound pressure level uncertainty (dB(A))                         | 3             |
| Supplied in  | Kitbox        |
| Vibration chiseling (m/s <sup>2</sup> )                          | 11            |
| Vibration chiselling uncertainty (m/s <sup>2</sup> )             | 2             |
| Vibration drilling (m/s <sup>2</sup> )                           | 12,5          |
| Vibration drilling into concrete [m/s <sup>2</sup> ]             | 12,5          |
| Vibration drilling into concrete uncertainty [m/s <sup>2</sup> ] | 2             |
| Weight (kg)  | 11,8          |

